

Serial No.: 09/836,514

Add the following claims:

36. (New) The method of claim 25 wherein the water-supplying compound reacts to form water.

37. (New) The method of claim 25 wherein the water-supplying compound and the water-reactive fuel precursor are included as contents contained in a first chamber and wherein said heating step comprises activating an initiator in discharge communication with the contents to form water.

38. (New) The method of claim 37 wherein at least a portion of the formed water reacts with at least a portion of the water-reactive fuel precursor to form a fuel material.


39. (New) The method of claim 37 wherein at least a portion of the water-supplying compound and at least a portion of the water-reactive fuel precursor are contained in the first chamber in direct contact.

Serial No.: 09/836,514

40. (New) The method of claim 37 wherein, in an at rest condition, the water-supplying compound is stored segregated from the water-reactive fuel precursor within the first chamber.

41. (New) The method of claim 37 wherein the first chamber is defined at least in part by a perforated housing.

42. (New) The method of claim 41 wherein a liner within the perforated housing maintains the first chamber contents in discharge proximity with the initiator.

 43. (New) The method of claim 25 wherein the water-reactive fuel precursor comprises an alkali metal.

44. (New) The method of claim 25 wherein the water-reactive fuel precursor comprises an alkaline earth metal.

Serial No.: 09/836,514

45. (New) The method of claim 25 wherein the water-supplying compound comprises an inorganic compound with stabilized waters of hydration.

46. (New) The method of claim 25 wherein the water-supplying compound comprises hydrated calcium oxylate.

47. (New) A method for inflating an inflatable safety device via an inflator device wherein a fuel material reacts to form gas generation reaction products, the method comprising:

*cont's* reacting a water-supplying compound contained within the inflator device to form water,

contacting a water-reactive fuel precursor contained within the inflator device with at least a portion of the formed water to form the fuel material in situ within the inflator device,

contacting the formed fuel material with a quantity of compressed gas, the compressed gas including a quantity of oxidant,

reacting at least a portion of the formed fuel material with at least a portion of the quantity of oxidant to produce heat,

Serial No.: 09/836,514

heating a stored quantity of inert gas with at least a portion of the produced heat to form an increased volume of gas and  
passing at least a portion of the increased volume of gas into the inflatable safety device to effect the inflation thereof.

48. (New) The method of claim 47 wherein the water-reactive fuel precursor is at least one metal element-containing material selected from the group consisting of:

hydrides, carbides, alkoxides and combinations thereof.

*cont'd*

49. (New) The method of claim 48 wherein the water-reactive fuel precursor comprises a metal alkoxide.

50. (New) The method of claim 49 wherein the water-reactive fuel precursor comprises an alkali metal.

51. (New) The method of claim 49 wherein the water-reactive fuel precursor comprises an alkaline earth metal.

Serial No.: 09/836,514

52. (New) The method of claim 47 wherein the water-reactive fuel precursor comprises at least one first component selected from the group of metals and organometallic compounds and at least one second component selected from the group of carbonates and bicarbonates.

53. (New) The method of claim 47 wherein the water-reactive fuel precursor comprises potassium t-butyl carbonate.

*A'*  
*cont'd*  
54. (New) The method of claim 47 wherein the water-supplying compound comprises ammonium nitrate.

55. (New) The method of claim 47 wherein the water-supplying compound comprises an inorganic compound with stabilized waters of hydration.

56. (New) The method of claim 55 wherein the water-supplying compound comprises hydrated calcium oxylate.

Serial No.: 09/836,514

57. (New) A method for inflating an inflatable safety device via an inflator device wherein a fuel material reacts to form gas generation reaction products, the method comprising:

reacting a water-supplying compound contained within the inflator device to form water, the water-supplying compound selected from the group consisting of ammonium nitrate and an inorganic compound with stabilized waters of hydration,

contacting a water-reactive fuel precursor contained within the inflator device with at least a portion of the formed water to form the fuel material in situ within the inflator device, the water-reactive fuel precursor selected from the group consisting of:

- A'*  
*cont'g*
- a) at least one metal element-containing material selected from the group consisting of hydrides, carbides, alkoxides and combinations thereof and
  - b) a carbonate-containing material,

contacting the formed fuel material with a quantity of compressed gas, the compressed gas including a quantity of oxidant,

reacting at least a portion of the formed fuel material with at least a portion of the quantity of oxidant to produce heat,

Serial No.: 09/836,514

heating a stored quantity of inert gas with at least a portion of the produced heat to form an increased volume of gas and

passing at least a portion of the increased volume of gas into the inflatable safety device to effect the inflation thereof.

58. (New) The method of claim 57 wherein the water-reactive fuel precursor comprises a metal alkoxide.

59. (New) The method of claim 57 wherein the water-reactive fuel precursor comprises an alkali metal.

60. (New) The method of claim 57 wherein the water-reactive fuel precursor comprises an alkaline earth metal.

61. (New) The method of claim 57 wherein the water-reactive fuel precursor comprises potassium t-butyl carbonate.

62. (New) The method of claim 57 wherein the water-supplying compound comprises ammonium nitrate.